



呼 称	記 号	B	F	C	D		A	E
					1 欄	2 欄		
A	B	Sch 80						
8A	1/4	14.3	23.0	10.0	9.4	7.8	11.1	21.1
10A	3/8	17.8	28.0	11.0	12.7	10.9	13.5	24.5
15A	1/2	22.2	33.0	13.0	16.1	14.3	15.9	28.9
20A	3/4	27.7	38.0	14.0	21.4	19.4	19.1	33.1
25A	1	34.5	47.0	16.0	27.2	25.0	22.2	38.2
32A	1 1/4	43.2	57.0	18.0	35.5	32.9	27.0	45.0
40A	1 1/2	49.1	63.0	19.0	41.2	38.4	31.8	50.8
50A	2	61.1	76.0	22.0	52.7	49.5	38.1	60.1
65A	2 1/2	77.1	96.0	26.0	65.9	62.3	41.3	67.3
80A	3	90.0	110.0	29.0	78.1	73.9	57.2	86.2
100A	4	115.4	138.0	35.0	102.3	97.1	72.5	107.5
A	B	Sch 160						
15A	1/2	22.2	38.0	14.0	12.3		19.1	33.1
20A	3/4	27.7	47.0	16.0	16.2		22.2	38.2
25A	1	34.5	57.0	18.0	21.2		27.0	45.0
32A	1 1/4	43.2	63.0	19.0	29.9		31.8	50.8
40A	1 1/2	49.1	76.0	22.0	34.4		38.1	60.1
50A	2	61.1	96.0 (84.0)	25.0 (23.0)	43.1		41.3	66.3 (64.3)
65A	2 1/2	77.1	110.0	28.0	57.3		57.2	85.2
80A	3	90.0	128.0	31.0	66.9		63.5	94.5
100A	4	115.4	146.0	32.5	87.3		75.0	107.5

( ) 内寸法はステンレス鋼に使用する場合があります。